

## The Advanced FTTH Splicer


**Active  
V-groove  
Alignment**



Single Fiber Fusion Splicer

# Fujikura 22S

Active V-groove Alignment



- Excellent for FTTH
- World's Smallest & Lightest Active V-groove Splicer
- Fast splicing time 9sec.
- Multi-Functional Carrying Case



# Fujikura 22S

## SPECIFICATIONS

Applicable fibers	Single / SMF(G.652/657), MMF(G.651), DSF(G.653), NZDSF(G.655)
Cladding dia./ Sheath dia.	125 μm / up to 3mm with sheath clamp
Cleave length	5mm to 16mm
Splice mode / heating mode	Total 100 splice modes / 30 heating modes
Typical splice loss	0.03dB (SM), 0.01dB(MM), 0.05dB(DS) and 0.05dB(NZDS) Measured by cut-back method relevant to ITU-T and IEC standards.
Splice time	Typical 9sec SM FAST, Typical 11sec SM AUTO
Tube heating time	Typical 24sec FP-03, coating dia.250μm Typical 25sec FP-03, coating dia.900μm Typical 19sec Slim60mm, Slim40mm coating dia.250μm
Splice result storage	Last 10,000 splices
Viewing methods / magnification	2 axis 2CMOS camera with 4.73" color LCD. 132X magnification.200X magnification after splicing
Tension test	1.96 to 2.25N
Applicable protection sleeve	60mm, 40mm and Fujikura micro sleeves
No. of splice / heating per battery full charge	Typical 200 cycles with BTR-11
Electrode life	3000 splices
Size / weight	120W x 189D x 72H mm / 1140g (including battery)
Operating condition	Altitude : 0 to 3,660m above sea level, Wind : 15m/sec Temperature : -10 to 50deg C, Humidity : 0 to 95%RH, non-dew
Other features	PC software upgrade / data management
Resistance feature	Shock resistance : 76cm (30inch) bottom surface drop <sup>*1</sup> Dust resistance : Exposure to dust ( 0.1 to 500μm dia. Alumina Silicate). <sup>*1</sup> Rain resistance : H=10mm/hr for 10min <sup>*1</sup>

\*1:Carried out in Fujikura labs in Japan.The shock resistance, dust resistance and rain resistance test do not guarantee that the product will not be damaged under these conditions.

## STANDARD PACKAGE

Description	Model No.	Q'ty
Fusion splicer	22S with BTR-11 and ELCT2-12	1pc
AC adapter	ADC-19	1pc
AC power cord	ACC-XX XX=08(JP),09(US),10(UK),11(EU),12(AU)	1pc
Carrying case	CC-32	1pc
Spare electrodes	ELCT2-12	1pair
Instruction manual CD	M-22	1pc
Quick reference guide	Q-22S-E	1pc
Alcohol pot	AP-01	1pc
Screw driver	SD-01	1pc

## OPTIONAL ITEMS

Description	Model No.
Fiber holder	FH-60-250 (coating dia. of 250μm)
	FH-60-900 (coating dia. of 900μm)
	FH-60-DC250 (coating dia. of 250μm in drop cable)
	FH-FC-20 (coating dia. of 900μm in 2.0mm Sheath dia.)
	FH-FC-30 (coating dia. of 900μm in 3.0mm Sheath dia.)
	FH-60-LT900 (900μm dia. loose buffer fiber)
Sheathclamp	CLAMP-S21A (included in standard package) CLAMP-S21B (900um dia. loose buffer fiber)
Battery pack	BTR-11(Li-ion)*2
Electrodes	ELCT2-12

\*2:all senders have to ovey the IATA regulation in case of Li-ion battery transportation by air.

## ACCESSORIES

Description	Model No.
High precision single fiber cleaver	CT-06 (for single fiber)
High precision fiber cleaver	CT-30 series (for single to 12 ribbon fibers)
Primary coat stripper	PS-02
Nylon jacket stripper	JS-01
Protection sleeve	FP-03 / 03 (L=40) and FPS01 series

## STANDARD PACKAGE



## OPTIONAL ITEMS



Please visit **NEW** web site!

<http://www.fusionsplicer.fujikura.com>

Facebook  
<https://www.facebook.com/FujikuraFusionSplicers>  
twitter  
<https://twitter.com/fujikurasplicer>

Specifications and descriptions are subject to change without prior notice.

## Fujikura Ltd.

1-5-1, Kiba, Koto-ku, Tokyo 135-8512, Japan  
Phone:+81-3-5606-1164 Fax:+81-3-5606-1534 <http://www.fujikura.com>

## Fujikura Asia Ltd.

438A Alexandra Road, Block A Alexandra Technopark #08-03 Singapore 119967  
Phone:+65-6-278-8955 Fax:+65-6-278-0965 <http://www.fujikura.com.sg>

## Fujikura Europe Ltd.

C51 Barwell Business Park, Leatherhead Road, Chessington, Surrey KT9 2NY, UK  
Phone:+44-20-8240-2000 Fax:+44-20-8240-2010 <http://www.fujikura.co.uk>

## AFL Telecommunications

260, Parkway East, Duncan, SC29334, USA  
Phone:+1-800-235-3423 Fax:+1-800-926-0007 <http://www.afglobal.com>

## Fujikura (China) Co., Ltd.

7th Floor, Shanghai Hang Seng Bank Tower, 1000 Lujiazui Ring Road, Pudong New Area, Shanghai, 200120 CHINA  
Phone +86-21-6841-3636 FAX +86-21-6841-2070