

RS1

Precision Resistance Standard

Includes 7 Resistances

10 Ω to 10M Ω in decade steps; others on request

Calibration Data

Comes with calibration data; different accuracy levels available

4-Wire Binding Posts

Uses gold plated copper (low EMF) or nickel brass binding posts with 4-wire connection

Low Temperature Drift

Low temperature coefficients, different versions available

Low Aging Rates

Different aging rate versions available

Temperature Sensor

PT100 temperature sensor included

Sealed Case

Prevents ingress of moisture by sealed case and special dissicant

ROHS

ROHS-compliant versions available

Optional Versions

Optionally possible are versions with other terminals, other resistances or other deviations from nominal; contact us



The RS1 is a cost efficient resistance Standard, intended e.g. for use in laboratory, research, metrology and educational applications where a precise yet economical resistance Standard is needed.

It comes in two basic versions, calibrated to different accuracy levels, both compliant to ROHS. The resistors used are high accuracy types in different precision and drift grades, depending on the version selected. The advanced version (-A) uses wirewound and film resistors, allowing for lower thermal and aging drift, and are e.g. intended for 6.5 and 7.5 digit DMMs. The highest precision (-H) version is based on hermetic, oil filled metal foil and film resistors with extremely low aging and temperature drift, for use as a Calibration Standard together with the most precise DMMs. The -H comes with low EMF gold plated Tellurium-Copper binding posts.

The case of the RS1 is sealed and uses a special dissicant to achieve a low internal humidity level, resulting in reduced humidity-induced drifts. Calibration is based on highly precise 8.5 digit DMMs, either used in absolute or in relative mode, using precision temperature-controlled resistance Standards with low uncertainties as reference. Calibration data is shipped with every item, attached to the Standard.

Besides the standard versions, custom resistance values can be made available, as well as versions with other binding posts. Please contact us through our website ab-precision.com.

Parameter	Details
Resistance	7 Decade Values, 10 Ω to 10M Ω
Operating Voltage	42V DC peak max. (SELV voltages <u>only!</u>)
Operating Temp.	18 – 28 °C (specified)
Connectors	4 binding posts per resistance (4-wire measurement) up to 1M Ω , 2-wire for 10M Ω
Order Code	RS1-A-R: Enhanced accuracy, ROHS RS1-H-R: Highest Accuracy, ROHS

RS1

Datasheet

Maximum Specifications at 23°C, K=2, unless otherwise specified:

Parameter	Condition	Specification
Ambient Conditions	Operation, per specification Operation, no damage Storage	18 – 28 °C 5 – 40 °C 5 – 50 °C
Deviation from Nominal *)1 *)2 *)5	RS1-A-R RS1-H-R	< 0,1% max. (10Ω: 0,2%) < 0.01% max. (10Ω: 0,1%)
PT100 Sensor Accuracy *)2 *)3)	18 - 28°C	< 0.25K max.
Maximum Power rating *)4	Per resistor	10mW
Resistor Material	RS1-A-R RS1-H-R	Wirewound (1MΩ/10MΩ: film) Hermetic foil (1MΩ, 10MΩ: film)
Working Voltage	All resistances	42V peak max. (SELV voltages!)
I/O Connectors	RS1-A-R RS1-H-R	Nickel plated brass Gold plated tellurium-copper
Weight	Average	Appr. 0.7kg

Notes:

*)1: relative to German National Standards.

*)2: relative to time and temperature of calibration and P < 10mW at all times; for temperature value see calibration data

*)3: within specified operating temperature range

*)4: although a higher load of up to 0,25W will not destroy the resistors, it will permanently degrade stability/drift.

*)5: for smaller deviations from nominal please contact us.

Please note that all specifications are typical values related to 23°C, unless otherwise specified.

For specified values, ambient temperature gradient shall be < 1K/h. Allow for sufficient stabilization time after high temperature changes.

To calculate total uncertainties, add calibration uncertainty, aging drift and temperature drift

RS1

Datasheet

Typical Specifications at 23°C, K=2, unless otherwise specified:

Maximum Calibration Uncertainty in ppm ^{*)1} ^{*)2}	10Ω	100Ω	1kΩ	10kΩ	100kΩ	1MΩ	10MΩ
RS1-A	25	20	15	15	15	20	65
RS1-H	9	6	3	3	3	7	20

Maximum Temperature Coefficient in ppm/K ^{*)3}	10Ω	100Ω	1kΩ	10kΩ	100kΩ	1MΩ	10MΩ
RS1-A ^{*)6}	3/5	3/5	3/5	3/5	3/5	5	5
RS1-H	3	1.5	1.5	1.5	1.5	5	5

Aging Drift in ppm/a ^{*)1} ^{*)2} ^{*)4}	10Ω	100Ω	1kΩ	10kΩ	100kΩ	1MΩ	10MΩ
RS1-A	5	5	5	5	5	10	20 ^{*)5}
RS1-H	2	1	1	1	1	10	20 ^{*)5}

Notes:

^{*)1}: relative to German National Standards. Actual calibration uncertainties will be given in the calibration data.

for tighter calibration uncertainties contact factory

^{*)2}: relative to time and temperature of calibration and $P < 10\text{mW}$ at all times; for temperature value see calibration data

^{*)3}: within the specified operating temperature range

^{*)4}: although a higher load of up to $0,25\text{W}$ will not destroy the resistors, it will permanently degrade stability/drift. Apply 10mW maximum!

^{*)5}: $\leq 50\text{ ppm/a}$ in the first year for 10M

^{*)6}: from 10Ω to 100kΩ TC is $\leq 3\text{ ppm/K}$ typical within the specified operating range, $\leq 5\text{ ppm/K}$ max over the full operating range

Please note that all specifications are typical values related to 23°C, unless otherwise specified.

For specified values, ambient temperature gradient shall be $< 1\text{K/h}$. Allow for sufficient stabilization time after higher temperature changes and fast temperature gradients to limit hysteresis effects.

To calculate maximum total uncertainties, add calibration uncertainty, aging drift and temperature drift contributions

RS1

Datasheet

Description:

The RS1 resistance standard consists of 7 precision, low temperature-drift decade resistors from 10Ω to $10M\Omega$, mounted in a sealed metal enclosure. Four-wire measurement terminals (2 wire for $10M\Omega$; but can be used in 4-terminal mode by using spade and banana connectors) are supported, eliminating the resistance of the measurement cable and binding posts. The sealed metal enclosure with guard connection reduces environmental electrical noise. The impact of humidity on the aging of the resistors is reduced by using a special dissiccant that keeps the internal humidity at a very low level. This improves aging especially for the -A version. Also, internal humidity-driven leakage currents are reduced. Enough dissiccant is included to support long term operation over many years, even assuming ingress of certain amounts of air (which can never be totally eleminated even with a sealing gasket) caused by air pressure changes.

The RS1 standard is available in four basic versions. The -A version uses wirewound resistors in lower ranges and special metal film resistors in high ranges. The -H version is based on hermetic, ultra low drift, oil filled metal foil resistors from 10Ω to $100k\Omega$ and special metal film resistor above. In addition, two different methods of calibration are used, resulting in different uncertainty levels. Calibration of the -A version is based on a precision 8.5 digit DMM. For the -H version calibration is performed in transfer mode, using a high precision 8.5 digit DMMs with specified low transfer uncertainties in conjunction with temperature-controlled resistance standards to achieve high calibration accuracies, resulting in the conservatively specified parameters indicated in the specification section above.

A PT100 is included for measuring the temperature of the resistors during calibration. The metal enclosure and low power operation results in a nearly zero temperature gradient between resistors and PT100, ensuring a precise temperature measurement (using 4-wire mode). Although the unit uses higher voltage components, because of its intended use and construction, it is specified for use with SELV (Safety Extra Low Voltage) voltages up to 40V DC maximum only and a 10mW power rating per resistance to ensure low drift rates.

Operation Precautions:

This product is a precision device and special care should be taken when operating it to achieve optimum performance. Always use 4-wire measurement techniques (up to $1M\Omega$), also for the PT100 temperature sensor, to avoid impacts of measurement cable resistance. Do not drop, handle carefully and ensure a temperature stabilized environment. Avoid any direct air drafts accross the item and high/fast thermal gradients (allow for sufficient stabilization time thereafter). Direct infrared radiation or other heat sources in close proximity to the unit should be avoided and will impact accuracy. Use short, shielded/twisted cables and avoid EMI-generating devices in close proximity to limit electrical interference and achieve maximum accuracy. Avoid temperature extremes whenever possible. Do not exceed the specified operating and storage conditions, otherwise damage may occure. Never apply a power greater than 10mW per resistor. Do not open item to avoid ingress of humidity. Use low EMF cables for the H-version and switch on thermal (EMF) voltage compensation on meters supporting this.

RS1

Precision Resistance Standard

Disclaimer and terms of Use:

1. All information included in this document was up-to-date as of the date this document was issued. Such information, however, is subject to change without any prior notice. Before purchasing or using any of our products, please confirm the latest product information with a sales representative. Also, please pay regular and careful attention to additional and different information as may be disclosed by us.

2. We do not assume any liability for infringement of patents, copyrights, or other intellectual property rights of third parties by or arising from the use of our products or technical information described in this document or on our website. No license, express, implied or otherwise, is granted hereby under any patents, copyrights or other intellectual property rights of us or others.

3. You shall not alter, modify, copy, or otherwise misuse or misapply any of our product, whether in whole or in part.

4. Descriptions of circuits and other related information in this document or on our website are provided only to illustrate the operation of our products and application examples. You are fully responsible for the incorporation of this information in your application. We assume no responsibility for any losses incurred by you or third parties arising from the use of this information.

5. When exporting the products or technology described in this document, you shall comply with the applicable export control laws and regulations and follow the procedures required by such laws and regulations. You shall not use our products or the technology described in this document for any purpose relating to military applications or use by the military, including but not limited to the development of weapons of mass destruction. Our products and technology may not be used for or incorporated into any products or systems whose manufacture, use, or sale is prohibited under any applicable domestic or foreign law or regulation.

6. We have used reasonable care in preparing the information included in this document, but we do not warrant that such information is error free. We assume no liability whatsoever for any damages incurred by you resulting from errors in or omissions from the information included herein.

7. Our products are classified as standard, not high quality products which are intended for applications such as computers; office equipment; communications equipment; test and measurement equipment; personal electronic equipment; and industrial equipment etc. Our products are not intended, and shall not be used, for applications such as Transportation equipment (automobiles, trains, ships, etc.); traffic control systems; anti-disaster systems; anti-crime systems; and safety equipment etc.

The use of our products in applications where any failure of such product, in whole or in part, could result, whether directly or indirectly, in personal injury or death of persons, is strictly prohibited. Applications where the malfunction of the product could result in defects of volume production items is prohibited. Products that we calibrate are not certified to comply with, nor do we claim to comply with the requirements of ISO/DIN or DAkkS calibration or the like. The use of these products for applications requiring such compliance is therefore prohibited.

Our products are neither intended nor authorized for use in products or systems that may pose a direct or indirect threat to human life or bodily injury (artificial life support devices or systems, surgical implantations, safety critical equipment, vehicles etc.), or may cause property damages (nuclear reactor control systems, military equipment, complex machine equipment etc.). We shall not be in any way liable for any damages or losses incurred by you or third parties arising from the use of any of our products in applications for which the product is not intended by us.

8. You should use our products described in this document or on our website within the allowable range specified by us, especially with respect to the maximum rating, operating supply voltage range, voltage range, heat characteristics, installation and other product characteristics. We shall have no liability for malfunctions or damages arising out of the use of our products beyond such specified ranges.

9. Although we endeavor to improve the quality and reliability of our products, electronic products have specific characteristics such as the occurrence of failures at a certain rate and malfunctions under certain use conditions. Further, our products are not radiation tolerant. Please be sure to implement sufficient safety measures to guard them against the possibility of physical injury, and injury or damage caused by fire in the event of the failure of our product, such as safety design for hardware including but not limited to redundancy, fire control and malfunction prevention, appropriate treatment for aging degradation or any other appropriate measures. Because the evaluation of hardware is very difficult, please evaluate the safety of the final products or system manufactured by you or applications you use our products in.

10. Please contact a sales representative for details as to environmental matters such as the environmental compatibility of each of our products. Please use our products in compliance with all applicable laws and regulations that regulate the inclusion or use of controlled substances, including without limitation, the EU RoHS Directive. We assume no liability for damages or losses occurring as a result of your noncompliance with applicable laws and regulations.

11. This information may not be reproduced or duplicated, in any form, in whole or in part, without prior written consent of us.

12. Please contact a sales representative if you have any questions regarding the information contained in this document, or if you have any other inquiries.

13. All product names are trademarks of their respective companies.